

Forenta

Morristown, TN U.S.A.

TENSION FORM FINISHER

Model 607TFF



- Finishes men's and ladies' coats, jackets, dresses, shirts, blouses
- Operates without tensioning for non-stretchable garments
- Operates with full tensioning when required
- Adjustable shoulder expanders
- Semi-automatic vent clamps close manually, automatic release at end of cycle
- Front and rear clamps for tensioning and non-tensioning garments
- Compact console with operational timers and switches
- Form raises additional 30 inches for longer garments
- Foot pedal controls:
 - Left pedal lowers form
 - Right pedal raises form
 - Center pedal activates front, rear clamps, automatic cycle
- Accessories – sleeve forms, water spray, front placket clamp

Specifications

Model 607TFF

Electrical connections		standard
208-230V 3PH 50/60Hz 8 amps 3.2kW		
380-415V 3PH 50/60Hz 4 Amps 3.2 kW with 220 volt neutral		optional
Steam, air and water connections		
Steam inlet	NPT	1/2"
Steam outlet	NPT	1/2"
Recommended steam pressure	psig	75-85
	kPa	517-586
Steam consumption @ 85 psig	lb/hr	69
Steam consumption @ 586 kPa	kg/hr	31
	BHP	2
Compressed air connection	NPT	3/8"
Recommended compressed air pressure	psig	65
	kPa	448
Compressed air consumption		
free air/cycle @ 65 psig		0.11 ft ³
free air/cycle @ 586 kPa		3.1 liter
Water connection (for water spray)	NPT	1/4"
Weight (crated)		
Shipping	lbs	400
	kg	182
1 Steam connection	4 Air connection	
2 Steam outlet	5 Electrical connection	
3 Control panel	6 Water connection	

