

Forenta

Morristown, TN U.S.A.

Laundry Apparel Press

Models A and ATA51VL/VLE

Models A and ATA53VL/VLE



A51VL/VLE



ATA51VL/VLE

- Insulated Head Cover and Nickel-Plated Head Reduces Heat Loss, Saves Energy
- Designed for Finishing Pants, Jackets, Pant Tops and All Wearing Apparel
- “A” Model Uses Control Bar Operation
- “ATA” Model Uses Two-Button Operation
- Available in Steam or Electric Versions

A53VL/VLE



ATA53VL/VLE





Specifications

Models A~ATA51VL / VLE, A~ATA53VL / VLE

Electrical connections	A51VL ATA51VL	A51VLE ATA51VLE	A53VL ATA53VL	A53VLE ATA53VLE
Voltage: 230V 1PH 50/60Hz	—	×	—	×
WATTAGE	—	4800W.	—	7400W.
Approx. Consumption/Hour	—	2.4 KWH	—	3.75 KWH
Steam and Air connection				
Steam Inlet	NPT 1/2"	—	1/2"	—
Steam Outlet	NPT 1/2"	—	1/2"	—
Rec. steam pressure	PSIG 100-125 kPa 621-861	—	100-125 621-861	—
Steam consumption	BHP 1 kg/hr 15.6	—	1 15.6	—
Compressed air	NPT 3/8"	3/8"	3/8"	3/8"
Air consumption	free air/cycle at 68psig free air/cycle at 470kPa	0,31 CU.FT. 8.8 liters	0,31 CU.FT. 8.8 liters	0,31 CU.FT. 8.8 liters
Rec. air pressure	PSIG 68 kPa 470	68 470	68 470	68 470
Weight (crated)				
Shipping	lbs 910 kg 413	910 413	940 426	940 426
Dimensions				
B (table width)	60"(1524)	60"(1524)	60"(1524)	60"(1524)
C (overall width)	A-Series 61"(1549) ATA-Series 60"(1524)	61"(1549) 60"(1524)	61"(1549) 60"(1524)	61"(1549) 60"(1524)
D	A-Series 34 1/2"(876) ATA-Series 34"(864)	34 1/2"(876) 34"(864)	34 1/2"(876) 34"(864)	34 1/2"(876) 34"(864)

- 1 Control bar ~for A-Series only
- 2 Control Push Buttons ~for ATA-Series only
- 3 Steam connection ~for steam heated models only
- 4 Air connection
- 5 Steam Outlet connection ~for steam heated models only
- 6 Electrical connection ~for electric heated models only



Detail Line Drawing (millimeters shown in parentheses)

